



Crystal Merchandiser® RVMC24, RVMC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4234	70"	3000, 3500, 4000	Left/Right	24 VDC	92	968 lm	8.8W	110
ChillBrite 4234	70"	3000, 3500, 4000	Center	24 VDC	92	2,024 lm	17.6W	115

Crystal Merchandiser® RVMC24 with French-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4234	70"	3000, 3500, 4000	Left/Right	24 VDC	92	1,795 lm	17.6W	102
ChillBrite 4234	70"	3000, 3500, 4000	Center	24 VDC	92	3,872 lm	35.2W	110

Highlight Merchandiser® RHMC30, RHLC30, RHCC30, RHZC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4190	62"	3000, 3500, 4000	Left/Right	24 VDC	90	792 lm	8.0W	99
ChillBrite 4190	62"	3000, 3500, 4000	Center	24 VDC	90	1,584 lm	16.0W	99

Crystal Merchandiser® RVLC30 & Highlight Merchandiser® RHMC30T, RHLC30T, RHCC30T, RHZC30T with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4190	67"	3000, 3500, 4000	Left/Right	24 VDC	90	864 lm	9.0W	96
ChillBrite 4190	67"	3000, 3500, 4000	Center	24 VDC	90	1,728 lm	18.0W	96

Reveal Merchandiser® with Doors ORMC83D & Highlight Merchandiser® RHCC24 with French-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4211	62"	3000, 3500, 4000	Left/Right	24 VDC	90	1,760 lm	17.6W	100
ChillBrite 4211	62"	3000, 3500, 4000	Center	24 VDC	90	3,520 lm	35.2W	100

Reveal Merchandiser® with Doors ORMC88D with French-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4211	67"	3000, 3500, 4000	Left/Right	24 VDC	90	1,920 lm	19.2W	100
ChillBrite 4211	67"	3000, 3500, 4000	Center	24 VDC	90	3,840 lm	38.4W	100

Features:

1. Anti-glare design.
2. Elegant appearance.
3. Bright and consistent illuminance of display area.
4. Less heat radiation, more energy saving.
5. Dimmable with PWM controller for additional energy savings.
6. Works with occupancy sensor SHE-B-96.
7. Lifetime: 50,000 hrs (Ta=95°F, 35°C).
8. IP Rating: IP65 (dust tight, protection from water jets).
9. Ta: -13°F to ~95°F (-25°C to ~35°C).
10. Material: Aluminum alloy.

Warranty:

1. LED Light: 5 Years Parts
2. LED Power Supply: 5 Years Parts

SS-60-G

Specifications are subject to change without notice.

11/16/2021