



Highlight Merchandiser® RHZC30T Tall Hybrid™ Specs

Low Temp Tall Hybrid™ Reach-Ins with 30" x 73" CoolView® Envision® Doors

RHZC30T: T=Tall

R-404A Refrigerant

R-448A Refrigerant

Standard Package

Refrigeration Data	
Refrigerant Charge (lbs.) ¹	
Zero Zone Condensing Unit #	
Condensing Unit Crated Weight (lbs.)	
Electrical & Energy Data ^{2,3,4}	
MOCP (amps) ⁵	
MCA (amps) ⁶	
Daily Energy Use (kWh)	
Rejected Heat (Btu/h) ⁷	
Electrical & Energy Data ^{2,3,4}	
MOCP (amps) ⁵	
MCA (amps) ⁶	
Daily Energy Use (kWh)	
Rejected Heat (Btu/h) ⁷	

2-Door	3-Door	4-Door	5-Door
5.1	5.9	6.5	8.0
69-10236	69-10236	69-10220	69-10220
150	150	180	180
With Condensate Removal System			
25	25	40	40
20.2	21.8	27.9	32.2
21.3	31.5	39.8	49.5
3,035	4,474	5,659	7,044
Without Condensate Removal System			
25	25	40	40
16.2	17.8	26.0	29.7
20.9	30.9	39.0	48.5
2,978	4,388	5,545	6,901

2-Door	3-Door	4-Door	5-Door
5.1	5.9	6.5	8.0
69-9929	69-10219	69-10219	69-10219
164	166	166	166
With Condensate Removal System			
20	35	40	40
16.6	25.5	30.8	36.9
25.1	30.6	40.4	50.3
3,570	4,355	5,748	7,154
Without Condensate Removal System			
15	35	35	35
11.9	22.5	24.6	30.7
24.7	30.0	39.6	49.3
3,512	4,269	5,634	7,012

High Humidity Package⁸

Refrigeration Data	
Refrigerant Charge (lbs.) ¹	
Zero Zone Condensing Unit #	
Condensing Unit Crated Weight (lbs.)	
Electrical & Energy Data ^{3,4,9}	
MOCP (amps) ⁵	
MCA (amps) ⁶	
Daily Energy Use (kWh)	
Rejected Heat (Btu/h) ⁷	
Electrical & Energy Data ^{3,4,9}	
MOCP (amps) ⁵	
MCA (amps) ⁶	
Daily Energy Use (kWh)	
Rejected Heat (Btu/h) ⁷	

2-Door	3-Door	4-Door	5-Door
5.1	5.9	6.5	8.0
69-10236	69-10220	69-10220	69-10220
150	180	180	180
With Condensate Removal System			
25	40	40	40
19.9	27.4	27.5	31.8
27.7	39.0	51.5	64.1
3,933	5,546	7,324	9,119
Without Condensate Removal System			
25	40	40	40
17.0	25.9	27.5	31.6
27.3	38.4	50.7	63.1
3,876	5,461	7,210	8,976

2-Door	3-Door	4-Door	5-Door
5.1	5.9	6.5	8.0
69-9929	69-10219	69-10219	69-10219
164	166	166	166
With Condensate Removal System			
20	35	35	35
16.2	25.2	26.6	31.8
31.8	38.7	51.2	63.7
4,526	5,508	7,274	9,056
Without Condensate Removal System			
15	35	35	35
12.7	23.7	25.3	31.6
31.4	38.1	50.4	62.7
4,469	5,422	7,159	8,913

Physical Data

Case Calculations	
Facings (ft. ²)	
Packout (ft. ³) 24" Shelves	
Weight (lbs.) ¹⁰	

2-Door	3-Door	4-Door	5-Door
30.0	44.6	59.3	74.0
60.0	89.3	118.7	148.0
891	1,141	1,451	1,791

2-Door	3-Door	4-Door	5-Door
30.0	44.6	59.3	74.0
60.0	89.3	118.7	148.0
891	1,141	1,451	1,791

Notes:

1. Refrigerant charge includes combined condensing unit and case charges.
2. Data based on Zero Zone ChillBrite® 5 LED lighting, Zero Zone CoolView® Envision® doors, and SSC electronic fan motors. See separate remote case spec sheets for more details.
3. 208V 4-wire service; 115/208V-1PH-60HZ; red & black power, white neutral, green ground. Buck/boost transformer available for low voltage conditions.
4. Optional main service disconnect is available upon request.
5. MOCP = Maximum over-current protection.
6. MCA = Minimum current amps.
7. Adequate ventilation must be provided to dissipate rejected heat from the top of the unit for proper


- performance. Clearance of less than 30" above the top of the shroud to the ceiling requires special design considerations. See Zero Zone Hybrid™ Installation & Operation Manual for specific details.
8. High Humidity Package includes high-wattage anti-sweat components that prevent condensation on doors and components in ambient conditions up to 85°F and relative humidity of 70%. An anti-sweat controller is required for DOE compliance.
9. Data based on Zero Zone ChillBrite® 5 LED lighting, Zero Zone CoolView® Envision® extra heat doors, and SSC electronic fan motors.
10. Does not include weight of condensing unit. Weights include 2 end panels at 60 lbs. per pair.




Highlight Merchandiser® RHZC30T Tall Hybrid™ Specs

Low Temp Tall Hybrid™ Reach-Ins with 30" x 73" CoolView® Envision® Doors

RHZC30T: T=Tall



# of Doors	Length	w/ 2 End Panels
2	62 1/8"	67 1/8"
3	92 1/2"	97 1/2"
4	123"	128"
5	153 3/8"	158 3/8"



SS-87-D

Specifications are subject to change without notice. All dimensions are nominal. Case designed to operate in an ambient temperature of 75°F and relative humidity of 55% or lower. See separate remote case spec sheets for additional details.

5/29/2020



Zero Zone, Inc.
800-247-4496 • www.zero-zone.com
© 2020 Zero Zone, Inc.

