



RMCP30SA SPECIFICATION SHEET

ELECTRICAL CONNECTION (B) & DRAIN (C) LOCATION SCHEDULE		
MODEL NUMBER	B	C
2RMCP30SA	48 5/8	31
3RMCP30SA	79 1/16	46 1/4
4RMCP30SA	109 1/2	61 1/2
5RMCP30SA	139 15/16	76 11/16

RMCP30SA CAPACITY SPECIFICATIONS			
CASE SIZE	SHELVING 29-5/8X 23-	CUBIC FEET CAPACITIES	WEIGHT*
	GROSS SQ. FT.	GROSS CUBIC FT.	POUNDS
2	48.3	59.6	625
3	72.5	88.8	923
4	96.6	118.1	1,178
5	120.8	147.3	1,490

WEIGHT BASED ON UNCRATED CASES WITHOUT ENDS, AND FULLY SHELVED.
SINGLE END WEIGHT: 54#

MODEL NUMBER	A	D	E	CONNECTIONS	
				INLET	SUCTION
2RMCP30SA	6 11/16	-	18 1/2	3/8 OD	5/8 OD
3RMCP30SA	21 7/8	-	17 3/8	3/8 OD	5/8 OD
4RMCP30SA	14 11/16	45 3/16	18 5/8	3/8 OD	5/8 OD
5RMCP30SA	17 5/16	70	18 1/2	3/8 OD	5/8 OD

ELECTRICAL SPECIFICATIONS BY DOOR MANUFACTURER									
MODEL NUMBER	FANS AMPS	T-12 LIGHT AMPS ONE END*	T-12 LIGHT AMPS BOTH ENDS	T-8 LIGHT AMPS	STD. DOOR	MULLION	FRAME	FRAMELESS DOOR	TOTAL FRAME MULLION STD. DOOR
ANTHONY DOORS									
2RMCP30SA	2.4	3.3	4.8	2.9	1.44	0.86	1.9	0	4.20
3RMCP30SA	4	4.8	6.6	3.88	2.16	1.72	2.24	0	6.12
4RMCP30SA	5.6	6.6	8.1	4.84	2.88	2.58	2.36	0	7.82
5RMCP30SA	6.4	8.1	9.6	5.82	3.6	3.44	2.82	0	9.86
ARDCO DOORS									
2RMCP30SA	2.4	3.3	4.8	3.78	0.52	1.08	0.72	0	2.32
3RMCP30SA	4	4.8	6.6	4.68	0.78	1.62	0.88	0	3.28
4RMCP30SA	5.6	6.6	8.1	6.12	1.04	2.16	1.06	0	4.26
5RMCP30SA	6.4	8.1	9.6	7.02	1.3	2.7	1.2	0	5.2
* STANDARD FOR CASE IN A LINE-UP									
VOLTAGE: 115 VOLTS 1 PHASE 60 HZ.									
BTU/HR ENERGY REQUIREMENTS: FOR PRODUCT TEMPERATURE OF 37°F TO 41°F WITH 20°F EVAPORATOR									
# OF DOORS	BTU/HR	BTU/HR RATING BASED ON 800 MA T-12 LIGHTING AND PARALLEL							
2	4,785	CASE DESIGNED TO OPERATE IN AN AMBIENT OF 75°F OR LOWER AND RELATIVE HUMIDITY OF 55% OR LOWER							
3	6,485								
4	8,140								
5	9,845								

Zero Zone, Inc. • 110 N. Oakridge Dr.
North Prairie, WI 53153-9792
1-800-247-4496 • FAX: 1-262-392-6450
www.zero-zone.com



All specifications are subject to change without notice.